

Items Supplied >

- 1 – SISSY BAR RACK
- 4 – M8 X 16MM BUTTONHEAD BOLTS

Application(s) >

FITS THE FOLLOWING COBRA SISSY BARS:

02-8607B-HONDA GROM 22-23, (SOLD SEPARATELY)

Instruction Manual >

02-3607B

Page 1 of 1

Read all instructions carefully and completely before installing your new Sissy Bar Rack!

1. Install the COBRA sissy bar first (sold separately, Part Number 02-8607B) per the installation instructions for that product.
2. Remove the rack and the bolts from the packaging.
3. Apply a couple drops of blue Loctite to the threads on the end of the bolts so they are ready for installation.
4. Carefully position the rack mounting brackets inside the sissy bar brackets and align the holes. The rack must come from underneath the sissy bar brackets to allow it to fit. See **FIGURE 1**.
5. Align the holes and insert the bolts through the sissy bar bracket and into the threaded holes in the rack. Snug the bolts but do not tighten at this time. See **FIGURE 1**.
6. Slowly tighten all the bolts a little at a time starting with the rear bolts first then the front bolts. See **FIGURE 1**.
7. Check the tightness of all the bolts after the first ride and after the first 500 miles.



FIGURE 1

To clean your black accessory use a liquid based soap detergent, such as dishwashing soap applied with a soft cloth and rinse with clean water. Note: Avoid abrasive cleaning methods such as granular or dry cleansers, simple green, Scotch-Brite or steel wool pads. Abrasives may breach the coating and shorten life.

* *Cobra® recommends you always wear a helmet while riding. Please never operate your motorcycle while under the influence of alcohol and/or drugs. Enjoy the new look of your motorcycle and please ride safely.*