



23801 E. La Palma Ave., Yorba Linda, Ca 92887 Ph. 714.692.8180 Fax. 714.692.5016

www.cobrausa.com

Items Supplied >

- 1 - Sissy Bar w/pad
- 2 - Brackets
- 4 - 8mm x 40mm Button Head Bolts
- 4 - 8mm x 16mm Button Head Bolts

Application(s) >

Kawasaki Vulcan 800A/B 95-05

Instruction Manual >

02-4920/02-5420/02-5920

Your sissy bar will install in just a few minutes using common tools. Read all instructions carefully and completely before installing your new sissy bar.

1. Remove the two (2) rear bolts on each fender rail.
2. Install the brackets with the bent portion (part number) toward the inside and tighten. Brackets will mount on the outside of fender rail.
3. Install the sissy bar to the brackets using the supplied hardware.

** Cobra recommends you always wear a helmet while riding. Please never operate your motorcycle while under the influence of alcohol and/or drugs. Enjoy the new look of your motorcycle and please ride safely.*

DOCUMENT NO. 0019 REV. A
10/03

Anything's Possible.



23801 E. La Palma Ave., Yorba Linda, Ca 92887 Ph. 714.692.8180 Fax. 714.692.5016

www.cobrausa.com

Items Supplied >

- 1 - Sissy Bar w/pad
- 2 - Brackets
- 4 - 8mm x 40mm Button Head Bolts
- 4 - 8mm x 16mm Button Head Bolts

Application(s) >

Kawasaki Vulcan 800A/B 95-05

Instruction Manual >

02-4920/02-5420/02-5920

our sissy bar will install in just a few minutes using common tools. Read all instructions carefully and completely before installing your new sissy bar.

1. Remove the two (2) rear bolts on each fender rail.
2. Install the brackets with the bent portion (part number) toward the inside and tighten. Brackets will mount on the outside of fender rail.
3. Install the sissy bar to the brackets using the supplied hardware.

** Cobra recommends you always wear a helmet while riding. Please never operate your motorcycle while under the influence of alcohol and/or drugs. Enjoy the new look of your motorcycle and please ride safely.*

DOCUMENT NO. 0019 REV. A
10/03

Anything's Possible.