COBRA.

23801 E. La Palma Ave., Yorba Linda, CA 92887 Ph. 714.692.8180 Fax. 714.692.5016

tems Supplied >	Application >	ww.cobrausa-vtwin
– FRONT MUFFLER ASSEMBLY – REAR MUFFLER ASSEMBLY	HARLEY: FATBOY FATBOY LOW BLACKLINE SOFTAIL DEUCE	07-17 10-16 11-13 2007
Instruction Manual >	6051	Page 1 of 1
 Remove the stock mufflers carefully and Position the stock clamps with hex head NOTE: THE MUFFLER WITH THE COBRA I head pipes until the mounting holes aligi Fasten the mufflers using the stock mounting the gap, where the mufflers meet the stock Check all clearances and alignments the 	nting bolts in the same manner as stock but do not ock heat shields, is similar to the gap the stock muff en tighten the clamps. (NOTE: The muffler clamps s ee Figure 2 . If the muffler clamps are slid forward p	on mufflers. he mufflers onto the tighten. Verify that lers allotted. should be flush with past the slots on the
 slots. The slots need to be covered by the necessary). 6. Tighten the mounting bolts to factory spectrum. 7. <i>IMPORTANT:</i> Before starting your engine 	remove all fingerprints from chrome with a quality wa pration. Due to fluctuations in fuel delivery settings, ti	tate the clamp if x or chrome polish.
 slots. The slots need to be covered by the necessary). 6. Tighten the mounting bolts to factory spectrum. 7. <i>IMPORTANT:</i> Before starting your engine Failure to do so can cause chrome discolution. 	ne clamp band so that it seals the slots properly. Ro ecifications. remove all fingerprints from chrome with a quality wa pration. Due to fluctuations in fuel delivery settings, ti ome discoloration. CLAMP S	tate the clamp if x or chrome polish. ming, etc., Cobra SHOULD BE VITH EDGE FLER CLAMP SPACER
 slots. The slots need to be covered by the necessary). Tighten the mounting bolts to factory sport of a starting your engine Failure to do so can cause chrome discold Engineering does not warrant against chromosometry of the starting to the start starting to the starting to the starting to the starting to t	The clamp band so that it seals the slots properly. Respectively and so that it seals the slots properly. Respectively a section of the slots properly and the slots properly. Respectively a section of the slots of the slots properly and the slots properly and the slots properly. Respectively a slot of the slots properly. Respectively a slot of the slot	tate the clamp if x or chrome polish. ming, etc., Cobra SHOULD BE VITH EDGE FLER CLAMP SPACER E 2