

Ite	ms Supplied >	Application(s) >
1 -	- Sissy Bar Rack	HONDA VLX600 98-07, ACE 750 98-03, SPIRIT 750 01-07, AERO 750 04-09, ACE1100/TOURER 95-99, VT1100 ALL (EXCEPT AERO), VTX1300C/R/S, VTX1800C/R/S/F 02-09 KAWASAKI VULCAN 800A 95-05 YAMAHA ROAD STAR 1600/1700 99-09
Instruction Manual >		
Ins	struction Manual >	02-3500
1.	Working on the right hand side of the motorcycle, rer support bracket. Set the bolts aside for reassembly.	nove the two bolts, which secure the sissy bar to the
1. 2.	Working on the right hand side of the motorcycle, rer support bracket. Set the bolts aside for reassembly. Carefully slide the sissy bar rack between the suppo	nove the two bolts, which secure the sissy bar to the ort bracket and sissy bar, aligning the holes.
1. 2. 3.	Working on the right hand side of the motorcycle, rer support bracket. Set the bolts aside for reassembly. Carefully slide the sissy bar rack between the suppor Install the bolts removed in Step 1 and finger tighten	nove the two bolts, which secure the sissy bar to the ort bracket and sissy bar, aligning the holes.
1. 2.	Working on the right hand side of the motorcycle, rer support bracket. Set the bolts aside for reassembly. Carefully slide the sissy bar rack between the suppo	nove the two bolts, which secure the sissy bar to the ort bracket and sissy bar, aligning the holes.

\* Cobra sissy bar racks are designed to fit with Cobra sissy bars only \* \* Cobra recommends you always wear a helmet while riding. Please never operate your motorcycle while under

the influence of alcohol and/or drugs. Enjoy the new look of your motorcycle and please ride safely.

04/01

 Items Supplied >

 1 - Sissy Bar Rack

 Wurk Cobrausa.com

 Wirk Cobrausa.com

 Virtual >

 Monda VLX600 98-07, ACE 750 98-03, SPIRIT 750 01-07, AERO 750 04-09, ACE1100/TOURER 95-99, VT1100 ALL (EXCEPT AERO), VTX1300C/R/S, VTX1800C/R/S/F 02-09

 KAWASAKI VULCAN 800A 95-05

 VAMAHA BOAD STAR 1600/1700 99-09

## Instruction Manual >

- 1. Working on the right hand side of the motorcycle, remove the two bolts, which secure the sissy bar to the support bracket. Set the bolts aside for reassembly.
- 2. Carefully slide the sissy bar rack between the support bracket and sissy bar, aligning the holes.
- 3. Install the bolts removed in Step 1 and finger tighten.
- 4. Repeat steps 1 through 3 on the left hand side of the motorcycle.
- 5. Tighten bolts to 12 ft. lbs.

\* Cobra sissy bar racks are designed to fit with Cobra sissy bars only \*

\* Cobra recommends you always wear a helmet while riding. Please never operate your motorcycle while under the influence of alcohol and/or drugs. Enjoy the new look of your motorcycle and please ride safely.

02-3500

Anything's Possible.